

ASSISTANT COMMISSIONER FOR PATENTS

WASHINGTON, D.C. 20231

ATTENTION: BOX PATENT APPLICATION

Sir:

Transmitted herewith for filing is the patent application of

Inventor: **James A. McKeeth**

For: **METHOD AND SYSTEM FOR COMMUNICATING BETWEEN CLIENTS IN A COMPUTER NETWORK**

Enclosed are:

- (X) Twenty (20) pages of specification.
- (X) Five (5) sheets of drawing.
- (X) Recordation form cover sheet with one (1)-page assignment.
- (X) A power of attorney form and copy of assignment.
- (X) Initial signed declaration by inventor.
- (X) Return prepaid postcard.



CLAIMS AS FILED

FOR	NUMBER FILED	NUMBER EXTRA	RATE	FEE
Basic Fee			\$690	\$690
Total Claims	28 - 20 =	8 ×	\$18	\$144
Independent Claims	5 - 3 =	2 ×	\$78	\$156
TOTAL FILING FEE		\$990		

- (X) A check in the amount of \$990 to cover the filing fee is enclosed.
- (X) A check in the amount of \$40 to cover the assignment recording fee.
- (X) The Commissioner is hereby authorized to charge any additional fees which may be required, now or in the future, or credit any overpayment to Account No. 11-1410. A duplicate copy of this sheet is enclosed.
- (X) Please use Customer No. 20,995 for the correspondence address.

Mark M. Abumeri
Registration No. 43,458
Attorney of Record

KNOBBE, MARTENS, OLSON & BEARA LIMITED LIABILITY PARTNERSHIP INCLUDING
PROFESSIONAL CORPORATIONS**PATENT, TRADEMARK AND COPYRIGHT CAUSES**

501 WEST BROADWAY

SUITE 1400

SAN DIEGO, CALIFORNIA 92101-3505

(619) 235-8550

FAX (619) 235-0176

INTERNET: WWW.KNOB.COM

LOUIS J. KNOBBE*
DON W. MARTENS*
GORDON H. OLSON*
JAMES B. BEAR
DARRELL L. OLSON*
WILLIAM B. BUNKER
WILLIAM H. NIEMAN
ARTHUR S. ROSE
JAMES F. LESNIAK
NED A. ISRAELSEN
DREW S. HAMILTON
JERRY T. SEWELL
JOHN B. SGANGA, JR.
EDWARD A. SCHLATTER
GERARD VON HOFFMANN
JOSEPH R. RE
CATHERINE J. HOLLAND
JOHN M. CARSON
KAREN VOGEL WEIL
ANDREW H. SIMPSON
JEFFREY L. VAN HOESEAR
DANIEL E. ALTMAN
MARGUERITE L. GUNN
STEPHEN C. JENSEN
VITO A. CANUSO III
WILLIAM H. SHREVE
LYNDA J. ZADRA-SYMES*
STEVEN J. NATAUPSKY
PAUL A. STEWART
JOSEPH F. JENNINGS
DRAIC S. SUMMERS
ANNEMARIE KAISER
BRENTON R. BABCOCK

THOMAS F. SMEGAL, JR.
MICHAEL H. TRENHOLM
DIANE M. REED
JONATHAN A. BARNEY
RONALD J. SCHOENBAUM
JOHN R. KING
FREDERICK S. BERRETTA
NANCY WAYS VENSKO
JOHN P. GIEZENTANNER
ADEEL S. AKHTAR
GINGER R. DREGER
THOMAS R. ARNO
DAVID N. WEISS
DANIEL HART, PH.D.
DOUGLAS G. MUEHLHAUSER
LORI LEE YAMATO
MICHAEL K. FRIEDLAND
STEPHEN M. LOBBIN
STACEY R. HALPERN
DALE C. HUNT, PH.D.
LEE W. HENDERSON, PH.D.
DEBORAH S. SHEPHERD
RICHARD E. CAMPBELL
MARK M. ABUMERI
JON W. GURKA
ERIC M. NELSON
ALEXANDER C. CHEN
MARK R. BENEDICT, PH.D.
PAUL N. CONOVER
ROBERT J. ROBY
SABING H. LEE
KAROLINE A. DELANEY
JOHN W. HOLCOMB

JAMES J. MULLEN, III, PH.D.
JOSEPH S. CIANFRANI
JOSEPH M. REISMAN, PH.D.
WILLIAM R. ZIMMERMAN
GLEN L. NUTTALL
ERIC S. FURMAN, PH.D.
TIRZAH ABE LOWE
GEOFFREY Y. IIDA
ALEXANDER S. FRANCO
SANJIVPAL S. GILL
SUSAN M. MOSS
JAMES W. HILL, M.D.
ROSE M. THIESSEN, PH.D.
MICHAEL L. FULLER
MICHAEL A. GUILIANA
MARK J. KERTZ
RABINDER N. NARULA
BRUCE S. ITCHKAWITZ, PH.D.
PETER M. MIDDLEY
THOMAS S. MCLENANAHAN
MICHAEL S. OKAMOTO
JOHN M. GROVER
MALLARY K. DE MERLIER
IRFAN A. LATEEF
AMY C. CHRISTENSEN
SHARON S. NG
MARK J. GALLAGHER, PH.D.
DAVID G. JANKOWSKI, PH.D.
BRIAN C. HORNE
PAYSON J. LEMEILLEUR
WILLIAM G. BERRY

OF COUNSEL
JERRY R. SEILER
JAPANESE PATENT ATTY
KATSUHIRO ARAI**
EUROPEAN PATENT ATTY
MARTIN HELLEBRANDT
KOREAN PATENT ATTY
MINCHEOL KIM
SCIENTISTS & ENGINEERS
(NON-LAWYERS)
RAIMOND J. SALENIEKS**
NEIL S. BARTFELD, PH.D.**
DANIEL E. JOHNSON, PH.D.**
JEFFERY KOEPKE, PH.D.
KHURRAM RAHMAN, PH.D.
JENNIFER A. HAYNES, PH.D.
BRENDAN P. O'NEILL, PH.D.
THOMAS Y. NAGATA
ALAN C. GORDON
LINDA H. LIU
YASHWANT VAISHNAV, PH.D.
MEGUMI TANAKA
ANDREW N. MERICKEL
CHE S. CHERESKIN, PH.D.**
ERIK W. ARCHBOLD
PHILIP C. HARTSTEIN
JASON I. SAATHOFF

* A PROFESSIONAL CORPORATION
* ALSO BARRISTER AT LAW (U.K.)
** U.S. PATENT AGENT

Assistant Commissioner for Patents
Washington, D.C. 20231

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Attorney Docket No. : MPATENT.164A

Applicant(s) : James A. McKeeth

For : METHOD AND SYSTEM FOR COMMUNICATING
BETWEEN CLIENTS IN A COMPUTER NETWORK

Attorney : Mark M. Abumeri

"Express Mail"
Mailing Label No. : EL 501 131 417 US

Date of Deposit : April 6, 2000

I hereby certify that the accompanying

Transmittal in Duplicate; Specification in 20 pages; 5 sheets of drawings; Declaration by
Inventor in 1 page; Recordation Form Cover Sheet and Assignment in 2 pages; Power of
Attorney by Assignee in 2 pages; Check for Filing Fee and Assignment Recordation;
Return Prepaid Postcard

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee"
service under 37 CFR 1.10 on the date indicated above and are addressed to the Assistant Commissioner
for Patents, Washington, D.C. 20231.

John Riedel

S:\DOCS\MMA\MMA-2192.DOC
040600

201 CALIFORNIA STREET
SUITE 1150
SAN FRANCISCO, CALIFORNIA 94111
(415) 954-4114
FAX (415) 954-4111

620 NEWPORT CENTER DRIVE
SIXTEENTH FLOOR
NEWPORT BEACH, CALIFORNIA 92660
(949) 760-0404
FAX (949) 760-9502

3801 UNIVERSITY AVENUE
SUITE 710
RIVERSIDE, CALIFORNIA 92501
(909) 781-9231
FAX (909) 781-4507

1875 CENTURY PARK EAST
SUITE 600
LOS ANGELES, CALIFORNIA 90067
(310) 407-5484
FAX (310) 407-5485

METHOD AND SYSTEM FOR COMMUNICATING BETWEEN CLIENTS IN A COMPUTER NETWORK

5 Background of the Invention

1. Field of the Invention

The invention relates generally to communication of information among clients and servers in a computer network, such as the Internet. More particularly, this invention relates to a method and system for communicating among clients over the Internet.

2. Description of the Related Art

With the explosive expansion in use of computer networks, such as the Internet, the demand for exchanging data, voice, and video has increased to record levels. Internet service providers (ISPs) continue to strive to keep up with the increased demand for service. To meet such demand, the Internet uses a system of numbers, known as an Internet protocol (IP) address, to identify every computer connected to the Internet. Generally, the IP address is an identifier for a computer or device operating on a transmission control protocol/Internet protocol (TCP/IP) network, such as the Internet. The format of an IP address is a 32-bit numeric address written as four numbers separated by periods. Each number may be within the range from and including zero to 255. Within a private network, an IP address may be assigned at random to each computer, as long as the IP address is unique to each computer. However, connecting a private network to the Internet requires using registered IP addresses (commonly referred to as “Internet addresses”) to avoid duplicate addresses for different private networks. The number of unassigned Internet addresses is running out, so a new scheme called Classless Inter-Domain Routing (CIDR) is gradually replacing the present IP addressing scheme.

A large number of users obtain access to the Internet from commercial ISPs via a dial-up telephone modem. In a technical sense, ISPs are considered private networks and, thus, an ISP assigns a predetermined number of IP addresses among its users using

any desired assigning method, such as dynamic host configuration protocol (DHCP). Thus, each time a user logs onto the ISP to connect to the Internet, the ISP assigns an IP address to the user to uniquely identify the user's computer ("client") to other users on the Internet worldwide. Knowing the IP address, any Internet user may contact the client by entering the IP address in its application, which is usually a data, voice, or video communication software. The process is very similar to day-to-day telephone number dialing. Knowing a telephone number, a telephone user may call the telephone number from any telephone unit around the world.

Typically, a local telephone company assigns a unique telephone number to a new telephone customer. The assigned telephone number is static, i.e., fixed and does not change during the duration of service. Thus, any telephone user may reach the new telephone customer by simply dialing the customer's telephone number. However, as described above, the IP address of an ISP client is dynamic (i.e., not static) and, thus, changes each time the client signs on to access the Internet. Accordingly, an Internet user cannot simply contact the client, because the client's IP address is unknown. Hence, each time an Internet user wishes to contact the client, the client must provide the Internet user with the client's *currently assigned* IP address. In view of the dynamic characteristic of the Internet, Internet users encounter limitations when desiring to contact or exchange live data with the client, e.g., voice or video conferencing.

Thus, there is a need in the computer network technology for a method and system that allow network users to communicate despite the dynamic character of IP addresses. Such method and system should allow users to communicate without having to know a client's IP address in advance.

Summary of the Invention

The invention provides a method of communication between a first client and a second client in a client-server network wherein the second client is allocated an interactive file. The method comprises identifying the second client with a first identifier of the second client. The method further comprises determining, based on the first identifier of the second client, a second identifier of the second client. The method further comprises establishing, based on the second identifier of the second client, a

communication link between the first client and the second client if the second client is connected to the network. The method further comprises establishing, based on the second identifier of the second client, a communication link between the first client and the interactive file of the second client if the second client is disconnected from the network.

In another embodiment, the method comprises accepting a request for communication with the first client via the network based, at least in part, on identifying the second client by an identifier that is equivalent to a network address of the second client. The method further comprises establishing, based on the network address of the second client, a communication link between the first client and the second client, if the second client is connected to the network. The method further comprises establishing, based on the network address of the second client, a communication link between the first client and the interactive file of the second client, if the second client is disconnected from the network. In another embodiment, the method comprises receiving from the second client a request for connecting to the network. The method further comprises communicating a network address of the second client to a server, which is configured to store the network address with an identifier of the second client. The method further comprises establishing, based on receiving the identifier of the second client from the first client, a communication link between the first client and second client, if the second client is connected to the network. The method further comprises establishing, based on receiving the identifier of the second client from the first client, a communication link between the first client and the interactive file of the second client, if the second client is disconnected from the network.

In yet another embodiment, the invention provides a system for communicating among a plurality of clients in a client-server network. The system comprises a first client that is configured to communicate with a second client via the network. The second client establishes communication with the first client by identifying the first client with a first identifier of the first client. The first client is allocated an interactive file. The system further comprises at least one server in communication with the first client. The server is configured to identify the first client by a second identifier of the client. The server is further configured to direct the second client to the first client when

the client is on-line, and direct the second client to the interactive file when the first client is off-line.

In yet another embodiment, the system comprises means for identifying the second client with a first identifier of the second client. The system further comprises means for determining, based on the first identifier of the second client, a second identifier of the second client. The system further comprises means for establishing, based on the second identifier of the second client, a communication link between the first client and the second client if the second client is connected to the network. The system further comprises means for establishing, based on the second identifier of the second client, a communication link between the first client and the interactive file of the second client if the second client is disconnected from the network.

Brief Description of the Drawings

The above and other aspects, features, and advantages of the invention will be better understood by referring to the following detailed description, which should be read in conjunction with the accompanying drawings, in which:

Figure 1 is a functional block diagram illustrating a plurality of computer networks connected via a communication network.

Figure 2 is a block diagram illustrating communication between an Internet user and an on-line client in accordance with the invention.

Figure 3 is a block diagram illustrating communication between an Internet user and an off-line client in accordance with the invention.

Figure 4 is a flowchart describing the process of establishing a connection by a client in one of the networks of Figure 1.

Figure 5 is a flowchart describing the process of handling a connection by an ISP server in one of the networks of Figure 1.

Detailed Description of the Invention

The following description is not to be taken in a limiting sense, but is made merely for the purpose of describing the general principles of the invention. The scope of the invention should be determined with reference to the claims.

Figure 1 is a functional block diagram of two or more computer networks 120 and 150 connected via a communication network 110. For the purpose of this disclosure, the combination of these two or more networks 110, 120, and 150 is referred to as the Internet 100. In principle, these networks operate in accordance with a client-server network architecture in which each computer or application on the network is either a client or a server. Thus, the network 120 comprises a plurality of clients 124, 126, and 128 that communicate to an Internet service provider (ISP) server 122 via respective dial-up modem links, or other similar links. Typically, each network includes at least one Domain Name System (DNS) server. Thus, the network 120 includes a DNS server 130 that is in communication with the ISP server 122 and the communication network 110. The DNS server provides a method of converting Internet domain names (e.g., www.site.com) to corresponding IP addresses (e.g., 121.132.143.154) to be understood by computer servers. This process is commonly referred to as "resolving" the domain name into an IP address. The DNS specification may be found in Request for Comments (RFC) 1035, authored by P. Mockapetris, and published by the Network Working Group (November 1987), and its subsequent revisions.

Similarly, the network 150 comprises a plurality of clients 154 and 156 that communicate to an ISP server 152 via respective dial-up modem links, or other similar links. The network 150 further comprises a DNS server 160 that is in communication with the ISP server 152 and the communication network 110. Although a limited number of ISP servers are shown in Figure 1, it is understood that ISPs often employ a plurality of servers that are configured for various applications. As indicated above, the ISP servers 122 and 152 provide access to other computer networks connected to the Internet 100. Although only a limited number of clients are shown in Figure 1, the shown clients are only illustrative of hundreds or thousands of clients. Typically, a client includes a personal computer (PC) or workstation on which users run applications. On the other hand, a server is a powerful computer dedicated to perform specialized functions, such as managing disk drives, printers, or network traffic. The server may be programmed with instructions to process client requests at least in part in accordance with the DNS specification.

009040 " 5364560

For a client (e.g., the client 124) to communicate with another client (e.g., the client 156), the client 124 may enter the IP address of the client 156 to establish a communication link with the client 156. However, as noted above, when the client 156 connects to the ISP server 152 via a dial-up modem link, a DHCP server (which may be the ISP server 152 or another ISP server) is likely to assign a different IP address to the client 156 each time the client 156 logs onto the ISP server 152. In this embodiment, it is desirable to assign a fixed and unique domain name (e.g., username.mwebpages.net) that uniquely identifies each client, e.g., the client 156. Thus, when the client 156 subscribes for or enters into service with the ISP, the ISP administrator determines a domain name that uniquely identifies the client 156 at all times, despite changes to the client IP address. The client may also subscribe for subdomain names such as worldwide Web (www), file transfer protocol (ftp), mail, and others.

In one embodiment, the ISP server 152 is configured to identify the client 156 with its unique domain name as follows. Once the client 156 dials up the server 152, the client 156 enters its identification information, such as a username and password to identify itself to the server 152. If desirable, such identification information may be encrypted using any available encryption method (e.g., secure socket link or SSL) to protect such information from access by computer hackers. Once the server 152 verifies that the identification information is valid, the DHCP server (e.g. server 152) assigns and transmits an IP address to the client 156 to identify the client 156 to other users of the Internet 100 during the log session.

The server 152 is configured to keep track of the IP address that is assigned to the client 156. More particularly, the server 152 is configured to update an IP address table in the DNS server 160 to correlate or match the domain name (e.g., username.mwebpages.net) of the client 156 with its latest IP address. Once a user sends a TCP/IP inquiry (e.g., packet) destined to the domain name of the client 156, the DNS server 160 resolves the domain name of the client 156 with the latest IP address. Thus, when any user (e.g., the client 126) wishes to establish a communication link with the client 156, the client 126 may simply identify the client 156 by its unique domain name, no matter what link the client 156 is using to access the ISP server 152, and no matter

how many different IP addresses the client 156 is assigned each time it connects to the server 152.

Figure 2 is a block diagram illustrating communication between an Internet user 224 and an on-line client 256 in accordance with the invention. In this embodiment, the Internet user 224 may be located in any network that accesses the Internet 100 (Figure 1), whereas the client 256 may be located in a different network. The client 256 may connect to the Internet via an ISP server 222 using a dial-up modem link. As noted above, the ISP network includes (or has access to) at least one DNS server 230 which is dedicated to resolving domain names into IP addresses. When the client 224 wishes to establish a communication link with the client 256, the client 224 may enter the domain name of the client 256. However, pursuant to the TCP/IP specification, it is necessary for the client 224 to identify the IP address of the client 256. As noted above, this identification is performed by "resolving" the domain name of the client 256, as described hereinafter.

DNS instructions are executed using a specialized software program, such as a Berkeley Internet Name Domain (BIND) software developed by the University of California, Berkeley. The BIND software is most commonly used by the server 222. The BIND software includes a server and a resolver module that allow clients to name resources and share this information with other servers in the network 200. Client applications, such as Web browsers, interact with the domain name space through ISP servers. The format of client requests and responses is specific to the local host and its operating system. Using a communication application, such as Microsoft NetMeeting, the client 224 is configured to request to be connected to (i.e., establish a link with) the client 256 by entering "username.mwebpages.net". To establish the link between the client 224 and the client 256, the DNS server 230 (or another DNS server) is configured to resolve the domain name username.mwebpages.net. The DNS server 230 responds to the client 224 by supplying the domain name-to-IP address conversion from a list of IP addresses available in an accessible memory (not shown in this figure). The memory is typically in the form of a cache memory that allows rapid access to the cached (i.e., stored) information.

To maintain a current list of IP addresses, the server 230 periodically establishes a link with one or more other DNS servers to acquire a copy of an up-to-date list of IP addresses or to check that an existing list has not changed. Also, the DNS server 230 caches one or more of the most recently resolved IP addresses from previous client transactions. Both of these techniques ensure that the server 230 has an up-to-date list of IP addresses as topology of the Internet changes. In this embodiment, the ISP server 222 is configured to update the list of IP addresses of the DNS server 230 in response to change in client on-line/off-line status. This feature is described in detail below.

Once the IP address of username.mwebpages.net is identified, the DNS server 230 communicates the IP address to the client 224, which in turn establishes a TCP/IP session with the client 256. Pursuant to the DNS specification, the entire "resolving" process is substantially transparent to the user. In other words, the user does not necessarily know that an IP address is resolved for the domain name.

Figure 3 is a block diagram illustrating communication between the Internet user 224 and the client 256 when the client 256 is off-line, in accordance with the invention. The block diagram of the network of Figure 3 is substantially similar to the network of Figure 2. When the client 224 enters the domain name of the client 256, the DNS server 230 is configured to resolve the domain name into an IP address of the client 224, as described above. When the client 256 is off-line, the ISP server 222 is configured to detect that the client 256 is off-line using any of the well-known methods. For example, in one embodiment, the server 222 is configured to periodically listen for an "alive" signal from the client 256. The alive signal may be in a form of at least one packet having any predetermined bit values to indicate that the client 256 is still connected to the Internet.

If no alive signal is received from the client 256 within a predetermined time interval (e.g., 10, 20, or 30 seconds), the server 222 transmits a verification signal to the client 256 to confirm that the client 256 is off-line. The verification signal may be in the form of a Packet Internet Groper ("ping") signal that determines whether a particular IP address is accessible. The verification works by sending a packet to the specified address (i.e., client 256) and waiting for a reply packet. If no reply packet is received from the client 256, the server 222 updates client information to indicate that the client

256 (i.e., username.mwebpages.net) is off-line. The server 222 is configured to re-
direct all client TCP/IP inquiries to an interactive file, such as a "Web page" of the
client 256. The Web page of the client 256 acts like an answering machine wherein
users wishing to contact the client 256 may leave messages to and retrieve information
5 from the Web page of the client 256, while the client 256 is off-line. The Web page
may be stored in the server 222 as part of the client's allocated or subscribed memory
space (e.g., 5 Megabytes) with the ISP. Thus, in this embodiment, the server 222 re-
directs the client 224 TCP/IP connection or session to the Web page of the client 256.
In other embodiments, the interactive file of the client 256 may include any desired
10 computer file, such as a streaming audio, video, an FTP server file, or a queuing mail
server file.

Figure 4 is a flowchart describing the process of establishing a connection by the
client 124 with the server 122 in the network 120 of Figure 1. In this embodiment, the
client 124 is configured to run an application software that communicates with the
15 server 122 when the client 124 is on-line. The process starts at block 400 when a user
of the client 124 runs a dial-up software to connect to the server 122. At block 404, the
client 124 requests connection to the Internet through the server 122, and connection is
granted after verifying that identification information of the client 124 is valid. At
block 408, the client 124 sends identification information and IP address of the client
20 124 to the DNS server 130. As noted above, the identification information may include
a username, password, and/or domain name. By sending such information to the DNS
server 130, the client 124 requests updating the table of IP addresses of the DNS server
130.

Once the identification information is verified to be valid, the client 124 receives
25 a queue message from the DNS server 130. The queue message indicates that the IP
address table of the DNS server 130 will be updated at the next scheduled update time.
Accordingly, the information and IP address of the client 124 is stayed in a queue until
the next update occurs. This ensures that the DNS server 130 is not interrupted each
time a new client logs onto the Internet. Information and IP addresses of all clients that
30 log onto the Internet within a predetermined time interval (e.g., 1, 2, or 3 minutes) are
used to update the IP address table of the DNS 130. At block 412, the client 124

displays the queue information to the user so that the user knows when he or she is expected to become accessible or reachable by other users who know the domain name of the client 124.

At block 420, the client 124 may retrieve announcements or other general informational messages from the server 122. At block 424, the server 122 connects the client 124 to the Web page of the client 124. As noted above, the Web page of the client 124 may include any desirable data. Thus, at block 428, the client 124 displays to the user information such as time of last log-on of the client 124, duration the client 124 was off-line, number of hits received by the Web page while the client 124 was off-line, any messages received from other users, and similar information. Thus, the user may retrieve, edit, and send any messages using the Web page. At block 432, the server 122 determines if the user wishes to edit or change the Web page of the client 124. If so, the operation proceeds to block 436 where the user is provided with an appropriate editor, such as a hypertext markup language (HTML) or plain text editor. In another embodiment, the client 124 may configure (i.e., edit or change) the Web page at any time, and not just at time of logging onto the server 122. As noted above, when the interactive file is expressed by media (e.g., audio or video) other than an HTML file, the client 124 may configure the interactive file using appropriate hardware/software, such as a microphone, headphone, and/or video camera. If, on the other hand, the user does not wish to perform any editing, the operation proceeds to block 440 where the user waits for server notification that the update of the DNS server 130 is successful.

Once the update of the IP address table of the DNS server 130 is complete, the operation proceeds to block 444 where the client 124 displays a message to the user indicating that the domain name "username.mwebpages.net" is live. This indicates that any user with access to the Internet may contact the user of the client 124 using the domain name of the client 124, despite a dynamically assigned IP address for the client 124. At block 448, the client 124 begins an alive loop with the server 122. As noted above, and as shown in block 452, a client 124 may run a software module that generates an alive signal (e.g., at least one TCP/IP packet) at periodic time intervals to notify the server 122 that the client 124 is still connected to the Internet. It is desirable to set the duration of the time interval long enough to avoid data transfer slowdown, but

short enough to promptly announce that the client 124 is off-line. At block 456, when the client 124 goes off line, the client 124 terminates the alive loop and sends an "off-line" message to the server 122. The process terminates at 460.

In one embodiment, one or more of the processes described in connection with the flowchart of Figure 4 may be implemented as software modules, or firmware in a processor, in the client 124, the ISP server 122, the DNS server 130, or any other server that is accessible by the ISP network 120. Although the description of the flowchart of Figure 4 is presented in connection with the client 124, it is understood that the flowchart may apply to any other client (e.g., the client 128) that accesses the Internet.

Figure 5 is a flowchart describing the process of handling a connection by the server 122 in one of the networks (e.g., the network 120) of Figure 1. The following describes operation of the network 120 at the server end. The process begins at block 500 when the DNS server 130 is powered on, reset, or the software application is run. The DNS server 130 includes (or has access to) at least three software modules that run in parallel (i.e., simultaneously). The three modules are represented by an update listening loop (block 502), a regular interval loop update (block 520), and an alive listening loop (block 540). Each branch of these loops is described separately hereinafter.

The update listening loop 502 represents a software module that allows the DNS server 130 to listen to new clients (e.g., the client 124 having a fixed domain name) that wish to log onto the Internet. When the client 124 wishes to update the DNS server 130 with the current IP address of the client 124, the user of the client 124 enters identification information. Thus, at block 504, the DNS server 130 receives the identification information and IP address from the user of the client 124. As noted above, identification information may include a username, password, and/or domain name. At this stage, it is assumed that the client 124 is already logged onto the Internet via the ISP server 122. Hence, the client 124 may communicate with the DNS server 130 via a TCP/IP socket connection. A socket commonly refers to a software object that connects an application to a network protocol, such as TCP/IP.

At block 506, the DNS server 130 determines whether the username and password are valid. If such information is not valid, the process proceeds to block 510

where the DNS server 130 notifies the user of the client 124 that identification information is not valid, and ignores the request of the client 124. If, on the other hand, the identification information is valid, the operation proceeds to block 508 where the DNS server 130 determines if the user of the client 124 is authorized to administer a domain name. This determination may be necessary because the user of the client 124 may have not subscribed for domain name service and, hence, may not have a fixed domain name. If so, the operation proceeds to block 510. If, on the other hand, the user of the client 124 is authorized to administer a domain name, the process continues to block 512 where the DNS server 130 queues the identification information and IP address of the client 124 until the next update of the IP address table of the DNS server 130.

At block 514, the DNS server 130 sends information to the client 124. The information notifies the user of the client 124 of the expected time of the next update of the IP address table of the DNS server 130. As noted above, this duration typically occurs within minutes. Meanwhile, as described in connection with the operation of the network 120 in Figure 4 above, the user of the client 124 may have access to his or her web page. At block 516, the operation of the DNS server 130 returns to the update listening loop described beginning at block 502.

The purpose of the regular interval update loop 520 is to update the IP address table of the DNS server 130 with most current IP addresses that correspond to the fixed domain names of subscribing clients. The regular interval update loop 520 of the DNS server 130 may operate as follows. At block 522, the DNS service of resolving IP addresses into domain names is halted or stopped temporarily, so that an update of the IP address table can occur. During the temporary stop of the DNS service, DNS service is routed to a backup DNS server (not shown in Figure 1) in accordance with the TCP/IP specification. As shown in Figure 5, the block 518 represents the queue (e.g., a memory space that is accessible by the DNS server 130) of DNS updates received from block 512. In another embodiment, the DNS service is not disrupted. To update the IP address table of the DNS server 130, DNS updates may be communicated to the DNS server 130 using an application program interface (API) call. As is well known in the art, API represents a set of routines, protocols, and tools for building software

applications. At block 524, the information that is present in the queue 518 is moved or transferred to a temporary queue (shown as block 528) to hold the latest DNS updates. This transfer empties and makes the DNS update queue 518 available for upcoming updates by new clients. At block 526, the IP address table of the DNS server 130 is modified or updated with the information from the temporary DNS queue 528. At block 530, the DNS service of the DNS server 130 is resumed.

At block 532, the DNS server 130 notifies users of all clients, whose identification information was present in the most recent temporary DNS update queue 528, that their information was processed successfully. This indicates to the user that the DNS server 130 is updated with the respective client's current IP address, so that other users may contact the respective client using its fixed and known domain name. At block 534, the temporary DNS update queue 528 is cleared or emptied, thereby making it available for holding next update information from the DNS queue 518. At block 536, the backup DNS server is updated with the latest IP address information currently present in the DNS server 130. Pursuant to the TCP/IP specification, updating the backup DNS server is an automatically timed event that occurs shortly after the primary DNS server 130 is updated. The regular interval update loop is temporarily terminated (at block 538) until the next update where the process returns to block 520.

The purpose of the alive listening loop 540 is to maintain an up-to-date record of the clients that are currently logged onto the Internet via the server 122. The alive listening loop 540 may operate as follows. At block 542, the server 130 listens to an alive signal (e.g., a TCP/IP packet) from each client that is logged onto the Internet via the server 122. At block 544, the server 122 determines whether such alive signal is received within a predetermined interval of time from each logged-on client. If so, the alive listening loop continues to block 552 indicating a return to the start of the alive listening loop at block 540. If, on the other hand, the alive signal is not received from a particular client (e.g., the client 124) within a predetermined time interval (e.g., 10, 20, or 30 seconds), the process continues to block 546 where the server 122 transmits a verification signal to the last known IP address of the client 124 to confirm that the client 124 is off-line. As noted above, the verification signal may be in the form of a ping signal that determines whether a particular IP address is accessible. At block 548,

the server 122 determines if the client 124 responds to the ping signal. If no reply packet is received from the client 124 at block 550, the server 122 updates client information to indicate that the client 124 (i.e., username.mwebpages.net) is off-line. The server 122 is configured to re-direct all client TCP/IP inquiries to the Web page of the client 124. Thus, in this embodiment, the server 122 re-directs future TCP/IP connection or session to the Web page of the client 124. The process continues to block 552, as described above. The block 590 indicates terminating the operation of the above-described loops and processes.

In one embodiment, one or more of the processes described in Figure 5 may be implemented as software modules, or firmware in a processor, of the ISP server 122, the DNS server 130, or any other server that is accessible by the ISP network 120. For example, the ISP server 122 may provide the above-described service to clients and, thus, no special software is needed to be implemented in the client 124. Although the description of the flowchart of Figure 5 is presented in connection with the network 120, it is understood that the flowchart may apply to any other network (e.g., the network 150) that accesses the Internet.

In view of the foregoing, it will be appreciated that the invention overcomes the long-standing need for a method and system that allow network users to communicate despite the dynamic character of IP addresses. Such method and system allow users to communicate without having to know a client's IP address in advance. The invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiment is to be considered in all respects only illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather by the foregoing description. All changes that fall within the meaning and range of equivalency of the claims are to be embraced within their scope.

WHAT IS CLAIMED IS:

1. A method of communication between a first client and a second client in a client-server network wherein the second client is allocated an interactive file, the method comprising:

5 identifying the second client with a first identifier of the second client;
determining, based on the first identifier of the second client, a second identifier of the second client;

establishing, based on the second identifier of the second client, a communication link between the first client and the second client if the second client is
10 connected to the network; and

establishing, based on the second identifier of the second client, a communication link between the first client and the interactive file of the second client if the second client is disconnected from the network.

2. The method as defined in Claim 1, wherein determining the second
15 identifier includes determining a network address of the second client based on a name of the second client.

3. The method as defined in Claim 1, further comprising communicating a name of the second client to a domain name system (DNS) server, and obtaining an Internet protocol (IP) address of the second client from the DNS server.

20 4. The method as defined in Claim 3, further comprising updating the DNS server with a current IP address of the second client, the IP address being identifiable by the domain name of the second client.

25 5. The method as defined in Claim 4, further comprising temporarily re-directing, when updating the DNS server, DNS service of the DNS server to another DNS server.

6. The method as defined in Claim 1, further comprising monitoring arrival of a signal that is periodically transmitted by the second client to the server, the arrival of the signal indicating that the second client is on-line.

30 7. The method as defined in Claim 6, further comprising determining that the second client is off-line if the signal is not received within a predetermined time interval.

8. The method as defined in Claim 1, wherein establishing a communication link between the first client and the interactive file includes accessing a Web page that is configured to provide information to the first client and allow the first client to leave a message to the second client.

5 9. The method as defined in Claim 8, further comprising allowing the second client to modify contents of the Web page.

10. A system for communicating among a plurality of clients in a client-server network, the system comprising:

10 a first client that is configured to communicate with a second client via the network, the second client establishing communication with the first client by identifying the first client with a first identifier of the first client, wherein the first client is allocated an interactive file; and

15 at least one server in communication with the first client, the server being configured to identify the first client by a second identifier of the client, and further configured to direct the second client to the first client when the client is on-line and direct the second client to the interactive file when the first client is off-line.

11. The system as defined in Claim 10, wherein the first identifier includes a name of the first client, and the second identifier includes a network address of the first client.

20 12. The system as defined in Claim 10, wherein the server comprises a domain name system (DNS) server that is configured to identify the first client by an Internet protocol (IP) address and, in response to receiving from the second client the domain name of the first client, communicate the IP address to the second client.

25 13. The system as defined in Claim 12, wherein the DNS server is configured to update an IP address table with a current IP address of the first client and identify the IP address of the first client based on the domain name of the first client.

14. The system as defined in Claim 13, wherein the DNS server is configured to temporarily re-direct, when updating the DNS server, DNS service to another DNS server.

15. The system as defined in Claim 10, wherein the server is configured to monitor arrival of a signal that is periodically transmitted by the first client to the server, the arrival of the signal indicating that the first client is on-line.

16. The system as defined in Claim 15, wherein the server is configured to determine that the first client is off-line if the signal is not received within a predetermined time interval.

17. The system as defined in Claim 10, wherein the interactive file includes a Web page that is configured to provide information to the second client and allow the second client to leave a message to the first client.

18. The system as defined in Claim 16, wherein the server is configured to allow the first client to modify contents of the Web page.

19. A system for communicating between a first client and a second client in a client-server network wherein the second client is allocated an interactive file, the system comprising:

means for identifying the second client with a first identifier of the second client;

means for determining, based on the first identifier of the second client, a second identifier of the second client;

means for establishing, based on the second identifier of the second client, a communication link between the first client and the second client if the second client is connected to the network; and

means for establishing, based on the second identifier of the second client, a communication link between the first client and the interactive file of the second client if the second client is disconnected from the network.

20. The system as defined in Claim 19, wherein means for determining the second identifier includes means for determining a network address of the second client based on a name of the second client.

21. The system as defined in Claim 19, further comprising means for communicating a name of the second client to a domain name system (DNS) server, and obtaining an Internet protocol (IP) address of the second client from the DNS server.

22. The system as defined in Claim 23, further comprising means for updating the DNS server with a current IP address of the second client, the IP address being identifiable by the domain name of the second client.

5 23. The system as defined in Claim 19, further comprising means for monitoring arrival of a signal that is periodically transmitted by the second client to the server, the arrival of the signal indicating that the second client is on-line.

24. The system as defined in Claim 23, further comprising means for determining that the second client is off-line if the signal is not received within a predetermined time interval.

10 25. A method of communication between a first client and a second client in a client-server computer network, wherein the second client is provided with an interactive file, the method comprising:

accepting a request for communication with the first client via the network based, at least in part, on identifying the second client by an identifier that is equivalent
15 to a network address of the second client;

establishing, based on the network address of the second client, a communication link between the first client and the second client if the second client is connected to the network; and


establishing, based on the network address of the second client, a
20 communication link between the first client and the interactive file of the second client if the second client is disconnected from the network.

26. The method as defined in Claim 25, wherein accepting a request includes identifying the second client by a name of the second client.

25 27. A method of communication between a first client and a second client in a client-server computer network, wherein the second client is provided with an interactive file, the method comprising:


receiving from the second client a request for connecting to the network;

communicating a network address of the second client to a server, which is configured to store the network address with an identifier of the second client;



—
G
—
L

col



۴۵۸




FIG. 3




FIG. 4

003040 6624450




FIG. 5

DECLARATION - USA PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;


I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled METHOD AND SYSTEM FOR COMMUNICATING BETWEEN CLIENTS IN A COMPUTER NETWORK; the specification of which is attached hereto;

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above;

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56;

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful, false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole inventor: **James A. McKeeth**

Inventor's signature 

Date 3-31-2000

Residence: **2625 South Stonehedge Drive, Nampa, Idaho 83686**

Citizenship: **U.S.A.**

Post Office Address: **2625 South Stonehedge Drive, Nampa, Idaho 83686**

Send Correspondence To:
KNOBBE, MARTENS, OLSON & BEAR, LLP
Customer No. 20,995

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO TAKE ACTION
AND
REVOCATION AND POWER OF ATTORNEY

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO
AND
REVOCATION AND POWER OF ATTORNEY

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is empowered to act on behalf of the assignor

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO TAKE ACTION
AND
REVOCAION AND POWER OF ATTORNEY

ESTABLISHMENT C

REVOCAT

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is empowe

Assistant
Washing
Dear Sir:
T

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO TAKE ACTION
AND
REVOCATION AND POWER OF ATTORNEY

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is empowered to act on behalf of the assignee below (the "Assignee").

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO TAKE ACTION
AND
REVOCATION AND POWER OF ATTORNEY

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is empowered to act on behalf of the assignee below (the "Assignee").

ESTABLISHMENT OF RIGHT OF ASSIGNEE TO TAKE ACTION
AND
REVOCATION AND POWER OF ATTORNEY

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is empowered to act on behalf of the assignee below (the "Assignee").


App. No. : Unassigned
Filed : Concurrently herewith

(949) 760-0404, **Customer No. 20,995**; also Steven P. Arnold, Registration No. 33,354, Hoyt A. Fleming, III, Registration No. 41,752, and Paul A. Revis, Registration No. 45,040, of Micron Electronics, Inc., 900 East Karcher Road, Nampa, Idaho 83687, Telephone (208) 898-3434 as its attorneys with full power of substitution and revocation to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected herewith. This appointment is to be to the exclusion of the inventor and his attorney(s) in accordance with the provisions of 37 C.F.R. § 3.71.

Please use **Customer No. 20,995** for all communications.

Micron Electronics, Inc.

Dated: 4/3/00

By: 
Paul A. Revis
Intellectual Property Counsel
900 East Karcher Road
Nampa, Idaho 83687

S:\DOCS\MMA\MMA-2151.DOC:dmr
031700